

PRODUCT INFORMATION SHEET

Model No		SMRCP-1058T
Brand		OEM
Product type		Android Tablet
Product Description		10.1" Digital Signage
 		
System	CPU	RK3568 Quad core cortex A55
	RAM	2GB
	Internal memory	16GB
	Operation system	Android 13
Display	Touch screen	10-Point capacitive touch
	Panel	10.1"LCD panel
	Panel Type	IPS
	Resolution	1280*800
	Display Colors	16.7M Colors
	Viewing angle	R/L 85/85, U/D 85/85
	Display mode	Normally black
	Contrast ratio	1500:1
	Response Time	25ms
	Back-light Type	ELed
	Luminance	280cd/m2
	Aspect Ratio	16:10
Network	WiFi	IEEE 802.11a/b/g/n/ac/ax
	Buletooth	Bluetooth 5.4
	Ethernet	10M/100M/1000M ethernet
Interface	SIM Slot	4G Flow Card
	SD Slot	SD card ,Max support to 64GB
	Earphone	3.5mm earphone + Microphone
	USB	USB 3.0 host
	USB	USB for serial (TTL Level)
	RJ45	Ethernet interface
	Micro USB	Micro USB OTG
Media play	Power jack	DC power input
	Video format	MPEG-1,MPEG-2,MPEG-4,H.265,H.264,H.263,VC-1,VP8,VP9,MVC, etc. 支持最大到4K视频
	Audio format	MP3/WMA/AAC/WAV/OGG, etc
	Photo	JPEG/PNG/GIF,etc
Other	Product Colors	White/Black
	VESA	75*75 mm
	Button	Power
	G-sensor	Support 90 degrees
	Speaker	2*2W
	Microphone	Single microphone
	NFC	Optional, 13.56MHz, ISO/IEC 18092, ISO/IEC 21481, ISO/IEC 14443 A&B, ISO/IEC 15693, Japanese Industrial Standard (JIS) (X) 6319-4, MIFARE Classic encrypted tags and cards
	RFID	Optional ,125k,ISO/IEC 11784/11785,EM4100, TK4100/GK4100
	LED light bar	LED light bar with RGB and mixed color
	Camera	Routine angle 5.0MP
	4G Moduel	Optional
	Language	Multi-language
	Certificates	CCC/CE/FCC
	POE	Support IEEE802.3at,up to 30W
Working Surrounding	Working Temperature	0℃---40℃
	Storage Temperature	-20℃---60℃
	Working Humidity	20~80%RH
	Storage Humidity	10~95%RH
Accessories	Adapter	Adapter,12V/1.5A
	User manual	*1

Drawing

